

FARGO® DTC4000

Direct-to-Card Printer

- ▶ **Highly versatile** – Delivering powerful printing and versatility in one modular and scalable design that simplifies equipment upgrades and migrations to higher levels of security.
- ▶ **Flexible footprint and design** – Its sleek and changeable footprint design makes the DTC4000 ideal for office environments where space is an issue.
- ▶ **Easy to use** – Intuitive design increases efficiency through easy set-up, loading and printing with an all-in-one print ribbon and card cleaning cartridge and SmartScreen™ graphical display.
- ▶ **Enhanced security** – Designed to migrate from lower to higher security levels, the DTC4000 offers standard printer password protection as well as fluorescent panel printing for a cost effective and dynamic increase in card security.



ACCESS versatility.

Designed for medium-sized business, schools and local government institutions seeking versatility in a convenient, professional and secure printer/encoder system, the DTC4000 is the ideal printer for organizations who need a flexible, easy and reliable way to color personalize and encode technology cards.

The DTC4000 not only meets your current needs, it also scales to meet your future requirements with these optional field-upgradable modules:

- ▶ Dual-sided printing module provides more space for card holder information and security features like duplicate photo and digital-signature.
- ▶ Optional same-side input/output card hopper and movable SmartScreen™ graphical display helps fit the printer into the tightest spaces.
- ▶ Increase capacity with a dual-input card hopper, holding 200 cards for higher capacity printing and encoding.
- ▶ Optional Ethernet connectivity allows for remote printer sharing by many users.
- ▶ Technology encoding modules encode data for magnetic stripe, proximity, contact and/or contactless technology cards, such as iCLASS®, for access control or other applications.

The DTC4000 combines a level of versatility with the simplicity to easily print what you need:

- ▶ SmartScreen™ graphical display provides easy-to-follow prompts to be sure you'll always know the status of the printer.
- ▶ Erase and rewrite eco-friendly feature makes the DTC4000 ideal for temporary ID cards.
- ▶ Industry's first inline card printing and technology card encoding with one connection using USB or optional Ethernet connectivity.
- ▶ Fully compatible with Asure ID® card personalization software for badge design, database management and technology card encoding.

The FARGO® DTC4000 is built with Genuine HID™ technology and is fully interoperable with other products in the HID ecosystem, enabling organizations to leverage their existing HID technology investments.

Specifications

Print Method	Dye-Sublimation / Resin Thermal Transfer
Resolution	300 dpi (11.8 dots/mm) continuous tone
Colors	Up to 16.7 million / 256 shades per pixel
Print Ribbon Options	<ul style="list-style-type: none"> • Full-color with resin black and overlay panel, YMCKO*, 250 prints • Full-color half-panel with resin black and overlay panel, YMCKO*, 350 prints • Full-color with two resin black panels and overlay panel, YMCKOK*, 200 prints • Full-color with fluorescing, resin black and overlay panel, YMCFKO*, 200 prints • Full-color with fluorescing, two resin black panels and overlay panel, YMCFKOK*, 175 prints • Resin black and overlay panel, KO*, 500 prints • Dye-sublimation black and overlay panel, BO*, 500 prints • Resin black (standard and premium), 1000 prints • Resin green, blue, red, white, silver and gold, 1000 prints • Rewrite technology- No ribbon is required
Print Speed**	7 seconds per card (K*); 12 seconds per card (KO*); 24 seconds per card (YMCKO*); 31 seconds per card (YMCKOK*)
Accepted Standard Card Sizes	CR-80 (3.375"L x 2.125"W / 85.6mmL x 54mmW); CR-79 Adhesive Back (3.313"L x 2.063"W / 84.1mmL x 52.4mmW)
Print Area	CR-80 edge-to-edge (3.36"L x 2.11"W / 85.3mmL x 53.7mmW); CR-79 (3.3"L x 2.04"W / 83.8mmL x 51.8mmW)
Accepted Card Thickness	.009" - .040" / 9 mil - 40 mil / .229mm - 1.016mm
Accepted Card Types	PVC or polyester cards with polished PVC finish; monochrome resin required for 100% polyester cards; optical memory cards with PVC finish; rewrite
Input Hopper Card Capacity	100 cards (.030" / .762mm)
Output Hopper Card Capacity	Up to 100 cards (.030" / .762mm)
Reject Hopper Card Capacity	Up to 100 cards (.030" / .762mm) - same-side input/output card hopper required
Card Cleaning	Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon change
Memory	32 MB RAM
Software Drivers	Windows® XP / Vista™ (32 bit & 64 bit) / Server 2003 & 2008 / Windows® 7 / Linux®
Interface	USB 2.0, optional Ethernet with internal print server
Operating Temperature	65° to 80° F / 18° to 27° C
Humidity	20–80% non-condensing
Dimensions	Single-Sided Printer: 9.8"H x 17.6"W x 9.2"D / 249mmH x 460mmW x 234mmD Dual-Sided Printer: 9.8"H x 18.2"W x 9.2"D / 249mmH x 475mmW x 234mmD
Weight	Single-Sided: 8 lbs. / 3.63 kg; Dual-Sided: 10 lbs / 4.54 Kg
Agency Listings	Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KCC
Supply Voltage	100-240 VAC, 3.3 A
Supply Frequency	50 Hz / 60 Hz
Warranty	Printer – Two years; Printhead – Two years, unlimited pass with UltraCard™
Encoding Options	125 kHz (HID Prox) reader; 13.56 MHz (iCLASS, MIFARE, ISO 14443 A/B, ISO 15693) read/write encoder; Contact Smart Card Encoder reads from and writes to all ISO7816 1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards; ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2 and 3
Options	Single Wire Ethernet and USB 2.0 interface for inline printing and encoding (note: single wire Ethernet encoding is only available for iCLASS® and contact smart card encoding); Dual-Sided Printing Module - Upgradable; Dual-Input Card Hopper (200 cards) - Upgradable; Same-Side Input/Output Card Hopper - Upgradable; Smart Card Encoding (contact/contactless) - Upgradable; Magnetic Stripe Encoding - Upgradable; Printer Cleaning Kit; Ethernet with Internal Print Server - Upgradable
Software	Swift ID™ Embedded Badging Application, FARGO Workbench Diagnosis Utility
Display	User friendly, SmartScreen™ graphical display
Printer Security	Printer access password protected; Kensington® lock compatibility

* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, O=Overlay, B=Dye Sublimation Black.

** Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.

This data sheet is for informational purposes only. HID Global makes no warranties, expressed or implied, in this summary. Company and product names and data used in sample output are fictitious. Specifications are subject to change without notice. Fargo and Asure ID are registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. This is not an offer of sale.

© 2010 HID Global. All rights reserved. HID, the HID logo, and FARGO are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

SL1499-Rev10B

fargo.hidglobal.com



Corporate North America
15370 Barranca Pkwy
Irvine, CA 92618
U.S.A.
Tel: 1 800 237 7769
Tel: +1 949 732 2000
Fax: +1 949 732 2360

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Tel: +852 3160 9800
Fax: +852 3160 4809

Latin America
Circunvalación Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Tel: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Haverhill Business Park
Phoenix Road
Haverhill, Suffolk
CB9 7AE
England
Tel: +44 1440 714 850
Fax: +44 1440 714 840